

CLW

4G/Multiband & WiFi Puck Antenna

Features

- Low Profile Puck Antenna
- 1 x 4G/LTE/Multiband element
- 1 x WiFi element
- Screw Mount

Specifications

	4G Multiband	WiFi
Frequency range	690-800/ 800-960 / 1710-2170 / 2500-2700 MHz	2400-2500 MHz
Peak Gain	2.0 / 1.0 / 4.0 / 3.5 dBi	2 dBi (typical)
Polarisation	Linear	Linear
VSWR	<2.5:1	<1.5:1
Power rating	10 W	10W
Impedance	50 Ohms	50 Ohms
Dimensions	102 x 33.5mm (dxh)	

Ordering Options

FCLW35312-SMRS-1K	CLW antenna with 2 x 1M RG174 and SMA-Male on 4G / RP-SMA on WiFi
FCLW35312-SMRS-2K	CLW antenna with 2 x 2M RG174 and SMA-Male on 4G / RP-SMA on WiFi

Specifications subject to change without notice.

5 Little Balmer
Buckingham Industrial Park
Buckingham
MK18 1TF
UK

REW@b S.r.l
C.F. e P.IVA 02026760351
Via Cipriani 2 - 42124 Reggio Emilia
Tel. 0522 420786 - Fax. 0522 420768
Email: marketing@reweb.it

EAD
embedded antenna design ltd
Delivering Antenna Innovation